

Product & Technical Specification 2022


Contents

Our Styles	3
Our Ranges	4
Shutter Colour Options	5
Product Options	6
Shutter Glossary	7
Frame Options	11
Panel Configuration	13
Product Limitations	14
Special Shape Shutters	15
Nuts & Bolts	20
The In's & Outs of Our Shutters	24
Key Facts Regarding Shutters	26

Our Styles

Full Height

Our most popular shutter which offers endless variations. Choose between 4 slat sizes, 3 materials, 4 control rod options and 28 colours. These shutters can be supplied with or without a dividing a mid-rail. Mid-rails provide added strength to taller panels and give enhanced flexibility in how you may control light and privacy (by adjusting the slats above the mid-rail independently to the slats below the mid-rail). It is also possible to request a break in some control rod options (concealed & hidden rods) This can offer that same flexibility without having the need for a mid-rail in the panel.



Whatever you decide please note that a full height panel will always open and close as one panel.

Full height is our best-selling style.

Café

Ideal for ground level windows or town houses. Café style leaves the top part of the window un-shuttered, using shutters only on the bottom part of the window. The panels often cover halfway up but they can be made to go up to any suitable position on the window. This style allows maximum light into the room yet provides privacy. However, consideration should be given to the function of the room. Bedrooms for example may need a curtain or blind to compliment café style shutters.



Tier on Tier


Two sets of shutter panels installed within the same frame, one set above the other. The top and bottom set open independently and this allows the greatest flexibility with controlling light and privacy. Tier on Tier shutters are generally suited to tall and narrower windows (think of a stable door). The split between tiers is generally requested in line with the top of a horizontal glazing bar present on the window. This style is very well suited to tall Victorian bay windows.



Solid Shutters

We offer a Solid Raised design for Full Height panels. These shutters are available from our **Hardwood** range and can be supplied either painted or stained (not in the Limewash finish) Solid shutters offer the best option for a near blackout solution in a room. You can choose to insert 1 or 2 Mid-rails in the solid panel as it is a good way to add extra detail.





Special Shapes

In the coming months we will offer a comprehensive range of shaped shutters. Available in **Hardwood**. Shaped windows can present a real challenge when it comes to window dressing, but we are confident that we can provide the perfect solution for every window. For peace of mind a technical drawing with dimensions will be provided for sign off before production begins. A surcharge applies to cover the additional work required at manufacturing. Shapes will be available to order via the shop soon but please speak to our team if you need support with a shaped order before then.



Our Ranges

Hybrawood

This shutter range is high quality and durable and available in 4 slat sizes,13 paints options, and with a choice of 4 control rod options. The outer bones of the shutter (frame, rails, and stiles) are constructed from Paulownia hardwood with ultradurable aluminium core running through each of the polyvinyl slats. This makes it significantly longer lasting than many other entry level shutters on the market. Built to last, these shutters are strong and will well age with time.

Hardwood

Paulownia wood has a fine and knot free grain which makes it the perfect hardwood for painting or staining. This hardwood shutter offers our full range of options – 13 paints, 11 wood stains and 4 limewash finishes. The Limewash finish clearly shows the woods grain through the paint and this range could be described as having quite a nautical/beach vibe. If your décor is rustic or shabby chic or you like a driftwood appearance then this could be the shutter for you. Visit our samples page to request a Limewash sample.

Although it's a hardwood Paulownia is approx. 1/3 lighter in weight when compared to other hardwoods. This makes it an excellent choice for Tier on Tier shutters or wider openings.

It's great for the environment too. A deep-rooted tree with a well-developed root system, it will yield one cubic meter of hardwood in 8 years, after which a new stem will shoot. A single plantation can therefore be harvested several times, providing a sustainable, renewable source of timber. Whilst the timber is light, its strong and will not crack or split when nails or screws are used.

Shaped shutters and Solid shutters are also available in Paulownia wood.

Waterproof Vinyl

For those areas of the home where windows are in <u>direct</u> contact with water you will need shutters that can stand up to the moisture and not warp over time. Our vinyl shutters are built to withstand the harshest of environments. They are 100% waterproof, will not fade, warp, or peel and the aluminium core running through the slat means they are highly durable.

Shutter Colour Options

Paints



Limewash



Stains




Product Options

Hybrawood	Hardwood	Hardwood Limewash Finish	Waterproof	
Vivid White TS05	Vivid White TS05	Limewash - White Grained TS40	Vivid White TS05	
Traffic White 9016	Traffic White 9016	Limewash - Fern TS30	Traffic White 9016	
Cream 9001	Cream 9001	Limewash - Branch TS31	Cream 9001	
Oyster White 1013	Oyster White 1013	Limewash - Bark TS32		
Grey White 0451	Grey White 0451			
Cream Grey 0452	Cream Grey 0452			
Brown Grey 0453	Brown Grey 0453			
Signal Grey 7004	Signal Grey 7004			
Dusty Grey 7037	Dusty Grey 7037			
Moss Grey 7003	Moss Grey 7003			
Traffic Grey 7043	Traffic Grey 7043			
Black Grey 7021	Black Grey 7021			
,	Beach White 0412			
	Old White 0411			
	Natural 0414			
	Honey 0415			
	Rustic Grey 0418			
	Chocolate 0416			
	Dark Chocolate 0417			
	Antique Brown 0419			
	Wenge 0421			
	Walnut 0420			
	Matte Black 0413			
Vivid White Hinge	Vivid White Hinge	Vivid White Hinge		
Natural White Hinge	Natural White Hinge	Natural White Hinge		
Off White Hinge	Off White Hinge	Off White Hinge		
Black Hinge	Black Hinge	Black Hinge		
Rub Bronze Hinge	Rub Bronze Hinge	Rub Bronze Hinge		
Brass Hinge	Brass Hinge	Brass Hinge		
Antique Brass Hinge	Antique Brass Hinge	Antique Brass Hinge		
Stainless Steel Hinge	Stainless Steel Hinge	Stainless Steel Hinge	Stainless Steel Hinge	
Slat Sizes 64mm 76mm 89mm 114mm	Slat Sizes 64mm 76mm 89mm 114mm	Slat Sizes 64mm 76mm 89mm 114mm	Slat Sizes 64mm 76mm 89mm 114mm	
Café Full Height No Tier on Tier	Café Full Height Tier on Tier	Café Full Height Tier on Tier	Café Full Height No Tier on Tier	
No Solid Shutters	Solid Raised Panels	No Solid Shutters	No Solid Shutters	
No Special Shapes	Special Shape Shutters	No Special Shapes	No Special Shapes	
Control Rod Options Central / Off set Rod Clearview / Hidden Rod	Control Rod Options Central / Off set Rod Clearview/ Hidden Rod	Control Rod Options Central / Off set Rod Clearview / Hidden Rod	Control Rod Options Central / Off set Rod Clearview/ Hidden Rod	

Note: Each 4 digit colour code is for manufacturing purposes. These codes are not representative of Ral or other retail paint brands.

Anatomy of a Shutter



Top and Bottom rails help to constuct the panel.

When slats are fully closed up, the Front Tilt Rod sits inside the Mouse hole.

The Front Tilt Rod connects all slats to allow them to close together. Moving the Front tilt will operate slats.

Shutter Slats come in 4 sizes. 64mm, 76mm, 89mm, 114mm.

A **Mid Rail** will add strength to taller panels. They offer flexibility on how the slats on top can be moved separately from the slats on the bottom.


The vertical rails on either side are called **Stiles**. Along with the top and bottom rails, they form the structure of the panel.

A **Clearview Tilt Rod** is a thin metal bar on the back of the panel. It connects all slats to allow them to close together. This option allows a more open view through the slats. From the front of panel, move any slat to operate all slats.

Hidden Tilt Rod - nothing visibly connects the slats. Tilt any slat and all slats move together.

Shutter Glossary

Panel Structure



Mortise and tenon joints are used when fixing Top & Bottom rails to the Stiles. This produces an extremely strong construction.

Mid Rails

Mid rails can also be referred to as divider rails. They give strength to taller panels. The 1st mid rail is required when a panel is over 1800mm. A second mid rail is required when a panel is over 2400mm. Always measure from the bottom up to the midpoint of your preferred location. Occasionally your requested location may need to move + or - by approx. half of one slat size. Allowing this flexibility helps manufacturing ensure that the optimum numbers of slats can fit in the panel height and achieve the smallest size of top and bottom rails.

Below is the amount manufacturing could move the mid rail location. The size of the mid rail for 64mm, 89mm & 114mm slats is a standard size of 76mm "tall". The size of the mid rail for 76mm slat is a standard size of 63mm "tall".

Wood & Hybrawood Shutters

Slat Size	MR can move by
64mm	+/- 25mm
76mm	+/- 32mm
89mm	+/- 38mm
114mm	+/- 50mm

Important: If you do not want your Mid rail location to move you must advise our team.

"Critical" ensures this will be the "Exact" Mid rail location. However, that could result in the panel receiving a bigger top or bottom rail which may aesthetically compromise your design. Please request a drawing before manufacture if in any doubt.

Note: **Critical** (Exact) mid rail requests are not an option for our Waterproof shutters range.

Top and Bottom Rails

When your shutters do not have a mid-rail, the top & bottom rails will always be the same size. The minimum size could be 76mm & the max size will be determined by your slat size.

We will always work to ensure the right balance ensuring the best aesthetics whilst ensuring structural integrity.

Wood & Hybrawood Shutters

64mm slat – max rail size is 127mm
76mm slat – max rail size is 140mm
89mm slat – max rail size is 153mm
114mm slat – max rail size is 178mm

Shutters **with a Mid Rail** could mean the Top & Bottom Rails are not always supplied the same size. The min size could be 76mm & max size will be determined by your slat size

Wood & Hybrawood Shutters

64mm slat – max rail size is 140mm 76mm slat – max rail size is 153mm 89mm slat – max rail size is 178mm 114mm slat – max rail size is 191mm

Waterproof shutters

The minimum size for the top & Bottom rails with our Waterproof range is 76mm and the maximum size is 117mm. Note: Requests for "Critical" (Exact) mid rails are not an option for this range.

Shutter Glossary

Slat Sizes










Your choice of slat will be dependent upon the look you are hoping to achieve. Generally, a small slat offers a more traditional look, whereas a bigger slat will offer a more contemporary look.

Solid shutters are available in Paulownia wood.

+ 10% for Solid Shutters


Tilt Rods



Central Front Tilt Rod

The front tilt rod is the vertical piece of wood which links the shutter slats together and allows all slats to open and close in unison.

A front tilt rod is normally located in the centre of the panel and perceived as the classic plantation shutter look.




Offset Tilt Rod

The offset tilt rod is the vertical piece of wood which links the shutter slats together and allows all slats to open and close in unison.

However, the offset position is 38mm from the edge of the slats on the hinged side of the panel.


+5% for this Rod Option



Clearview Tilt Rod

A Clearview tilt rod is the term given to shutters that have a discreet aluminium tilt rod hidden at the rear of the shutter panel.

To open and close the slats you simply adjust any one of the slats and all slats attached to that rod will open in unison. Please note there is no surcharge for the Clearview tilt.



Hidden (In Stile) Tilt Rod

The In Stile tilt rod is completely hidden within the panel's stile. To open and close slats simply adjust any one of the slats attached to the In-Stile mechanism and all slats open in unison.

+ 10% for this Rod Option

Clearview Split

Shutters taller than 1300mm without a mid-rail require a split in the Clearview tilt rod. You can request a split in a specific location. Always measure from the bottom up for the split location. If no location is requested then your order will automatically receive a split in the centre of the Clearview rod. Having a split in Clearview rods over 1300mm helps ensures good slat closure.



Clearview option for all ranges.


Hidden (In Stile) Tilt Rod

Slat Size	Qty of slats
64mm	20
76mm	17
89mm	14
114mm	11

Shutter Glossary


Butt Stile

Single panels always receive a butt stile on both sides of the panel. When more than 1 panel, the side of the panel that is hinged onto the frame will always have a butt stile.



Rabbet Stile


All panels (Bi-fold or Tri-fold) receive rebated stiles where there are hinges. The rebate design helps to reduce the light gap in between panels.



Astragal Stile

All meeting panels receive an Astragal on the right opening panel as standard. This covers any light gap between meeting L/R panels. You can advise our team if you prefer to have the Astragal on the left opening panel.

Where possible, when a panel configuration has an uneven number of panels (LLR) manufacturing will supply a second Astragal to offer symmetry to the design. However on some configurations an Astragal could restrict the panels folding so a rebated stile will be supplied.



Frame Options

Wood & Hybrawood

Inside Mount -



Plain L60mmTechnical Drawing

Plant Alberta Streets


Templates in measure guide

Plain L60mm




Frame as shown in shop

Plain L60mm



Bullnose Z Frame




Bullnose Z Frame




Bullnose Z Frame

Outside Mount -



Vintage L70mmTechnical Drawing



Vintage L70mm with Build outs




Vintage L70mm

Top Tip: Vintage L70mm can be supplied with a **frame build out** to allow you achieve L80mm, L90mm, L100 mm deep frame. Please add the request for a frame build out into the **special notes** in your order and advise our team on the "checking your order" phone call..


Frame Options

Waterproof

Inside Mount -





PV Plain L60mm Technical Drawing




PV Bullnose Z Technical Drawing

Templates in measure guide







PV Bullnose Z

Frame as shown in shop




PV Plain L60mm



PV Bullnose Z

Outside Mount -



Vintage L70mm Technical Drawing



PV Vintage L70mm



PV Vintage L70mm

Panel Configuration


When ordering, always input your panel requirements from left to right e.g. LLRR

T Posts

Larger windows can be divided into segments using T posts. Panels can be hinged off a T post or multiple T posts.

Always measure from left to right and your dimension should be inclusive of where your frame will be on the left side.

For 1 vertical T post - measure from left to right to the required location of a T post - an example layout would be LRTLR. For a 2nd vertical T post - measure again from the left to the required location of the 2nd T post. e.g. LTLRTR. For a horizontal T post - measure from the bottom up to the required location of the horizontal T post.




Bay Windows

Individual Frames

Angled Bay windows can be fitted with individual frames. Box Bay windows can be fitted with individual frames and square corner posts.

Posts are available at 48mmx48mm, 58mmx58mm, 68mmx68mm, 78mmx78mm or 88mmx88mm



2500mm - 3000mm

5 Hinges

	Hybraw	ood - Panel size	only - Does	not include fra	me		
		Width					
	Min Max			Height			
Shutter Style		Single Hung	Bi-Fold	Tri-Fold(3)	Min	Max	
64mm 76mm 89mm 114mm	200mm	890mm	600mm	N/A	250mm	2950mm	
	Paulownia	Wood - Panel si	ze only - Do	es not include f	rame		
		Width					
	Min		Max		Height		
Shutter Style		Single Hung	Bi-Fold	Tri-Fold(3)	Min	Max	
64mm 76mm 89mm 114mm	200mm	890mm	660mm	450mm	250mm	2950mm	
Solid Panels (shaker /raised)	200mm	660mm	660mm	450mm	250mm	2950mm	
Special Shapes	200mm	890mm	660mm	450mm	250mm	2950mm	
	Waterproof S	Shutters - Panel	size only - [Does not includ	e frame		
		Width					
	Min		Max		Height		
Shutter Style		Single Hung	Bi-Fold	Tri-Fold(3)	Min	Max	
64mm 76mm 89mm 114mm	200mm	700mm	500mm	N/A	250mm	2950mm	
		Control	Rod - Split	s			
	ntrol split require						
Maximum Slats possibl	e to connect toge	ether 64mm = 20) slats 76mr	m = 17 slats 89	mm = 16 slats	s 114mm = 11 slats	
		Mi	d Rails				
Panel over 1800mm -						move up or down 6mm slat +/- 31mm	
Panle over 2400mm - Mid Rail Size i	2nd Mid Rail Red always 76mm	quired	89mm slat +/- 38mm 114mm slat +/- 50mm Select EXACT Mid Rail location and the position will not move				
	Maximum n	umber of panel	s hinged fro	om one side of	frame		
Style	Hybra		Wood		Wood Wate		Waterproof
Full Height	2		3			2	
Café	2		3		2		
Tier on Tier	N/A		3			N/A	
Number of Hinges pe	r Panel	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	Wood T-Po:	Vood T-Post		Vaterproof T-Post	
Up to - 1300mm	2 Hinges		16, 25.4 16 821 93			25,4	
1300mm -1800mm	3 Hinges		261			3.33 9.38 15.39 12.39	
1800mm - 2500mm	4 Hinges	_	57.4 T-Post-50			44,15	
2500mm - 3000mm	5 Hinges		T-Post-50			PVC T_PRST	

T-Post-50 Wood & Hybrid T Post

PVC T-POST

Special Shape Shutters


Speciality shaped windows make a stunning addition to any room, but they can be difficult to dress. Bespoke shutters are the perfect solution. Before you design, survey and order please read through our guide so that you have a clear understanding on the special shape shutters we supply. A surcharge and slightly longer lead time applies.

Before you begin


- 1. Shapes are available in our Hardwood range only.
- 2. Each shape has a dedicated name. Use the 'Special Notes' box at the end of order to reference the required shape name. Include additional A, B, C measurements where guide suggests.
- 3. We request you upload a clear photo of your shaped window when you submit your order.
- 4. We will provide a detailed manufacturing drawing for you sign off before production begins.
- 5. Certain shapes require that slats must be operated by hand (Arch1, Arch2, Circle3, Sunburst 1, Elongated Sunburst 1)

Let's get started.


Arches, Circles and Sunburst shapes are supplied as symmetrical. This means the left side is the same as the right side. You can confirm that your window is symmetrical if the height of the Arch is exactly half the width of the base. We cannot supply non perfect shapes.



For Height, measure from the very centre of the width up to the highest point of arch.




Circle 1 – 2 x panels hinge as R**T**L Circle 2 & Circle 3 panel is held in frame via magnets



For Height, measure from the very centre of the width up to the highest point.


Measure A on both sides and select the smallest A dimension you find.

Sunburst panels can hinge on the bottom to open downwards.





Tapered shapes need an additional measurement which is B.



Tip - Adding a T post within a shaped frame is a good option when the window is very wide. Please discuss this with our expert team.



Important

Depending on your window type, please also read the relevant guide for a **Recess** or **Non-Recess** window. These guides contain paper frame templates to use whilst surveying and comprehensive information on measuring.

As per these measure guides we recommend making a small deduction to your sizes for your shaped shutter frame. Deductions allow a little wiggle room during the installation.

- We offer 2 frame options for inside mounting: L frame & Z frame.
- We offer 1 frame option for outside mounting: L frame.
- Z frames can have the overhang lip removed on the bottom if you have a protruding sill. This is called a sill cut.
- L frames can request buildouts when you need a deeper frame due to your slat size or a handle obstruction.

Finally, be mindful of where you plan to position **Arch 2 & Arch 4**. Arch top panels must be able to move freely without catching on the top of any recess or sloped ceiling. Often fitting the frame for Arch top panels at the front of the recess is best. Alternatively **Arch 1** and **Arch 3** can work better if you prefer to fit your shutter tight to window within a recess because the Arch sunburst section opens down.

Our team will be happy to advise you.

Hinges



Paint Options	Best Hinge Options				
Vivid White	Vivid White or Natural White	Brass	Antique Brass	Rub Bronze	Stainless Steel
Traffic White	Natural White	Brass	Antique Brass	Rub Bronze	Stainless Steel
Cream	Off White	Brass	Antique Brass	Rub Bronze	Stainless Steel
Oyster White	Off White	Brass	Antique Brass	Rub Bronze	Stainless Steel
Cream Grey		Brass	Antique Brass	Rub Bronze	Stainless Steel
Grey White		Brass	Antique Brass	Rub Bronze	Stainless Steel
Brown Grey		Brass	Antique Brass	Rub Bronze	Stainless Steel
Signal Grey		Brass	Antique Brass	Rub Bronze	Stainless Steel
Dusty Grey		Brass	Antique Brass	Rub Bronze	Stainless Steel
Moss Grey		Brass	Antique Brass	Rub Bronze	Stainless Steel
Traffic Grey		Brass	Antique Brass	Rub Bronze	Stainless Steel
Black	Black	Brass	Antique Brass	Rub Bronze	Stainless Steel

Rule for Hinges

Panel ≤ 1300mm = 2 hinges

Panel 1300mm - 1800mm = 3 Hinges

Panel 1800mm - 2500mm = 4 Hinges

Panel 2500mm - 3000mm = 5 Hinges



Hinge Placement

From the end of a panel to the middle of the 1st hinge will always be 138mm

Slimline Hinge




Slimline hinges are used between rebated stiles. These are available in all hinge colours.

Flat Hinge



Used on Butt and Astragal Stiles

Gaps for Hinges & Clearance



Magnets

Shutters are supplied with small round magnets which are pre inserted into the back of the panel's stile. Wood & Hybrawood frames receive a round magnet strike plate which is pre fitted to the frame. The magnet plate colour will match the colour of the hinge.



Orders with a 3 sided frame will receive a separate light stop with magnet plates attached. These orders will also receive striker magnet plates in the hardware box. The fitter can choose to use either option if necessary during the installation.







Waterproof frames receive a flat-bottom round white magnet which is pre fitted to the frame.

Knobs

Solid shutters will have 2 x small chrome knobs supplied per line. These will not be pre fitted to the panels but supplied in the hardware box.



Clearview Tilt Rod



The straight Clearview Rod is available for all ranges.

Hidden Rod-Instile



Available for all ranges.

Hoffman Key



There are 2 x sizes, 27mm & 36mm. These plastic keys are pre inserted at manufacturing into both mitred ends of the top and bottom frame pieces. This allows for easy assembly of the entire shutter frame.

Hinge Packer



The hardware box will contain 1 packer per hinge as per the total order.

Tension Screw Access

Panels are supplied with the tension screw holes on the side of the panels.

These holes allow access to adjust the slat tension. Insert a cross head screwdriver into both tension holes either side of the panel



It is standard practice to leave these holes open. If required Tension holes can be covered using the coordinating plastic caps provided in hardware box. Caps are shaped for Butt and Rebated holes.

Spare Slats & Fixing

and twist in opposite directions.


There is 1 x spare slat per line supplied in the frame box. For a single panel, the frame & panel & spare slat will be supplied together in one box. For the shutter where all panels are the same width, 1 x spare slat will be supplied. For the shutter with T-posts & panels of different widths, 1 x spare slat per panel width will be supplied.

Please see images below to understand the type of fixings that are supplied with spare slats. Replacing slats is very straight forward and our team can mail you a short video to explain how it is done.

Central & Off-set Tilt Rod



Hidden Instile Rod



Clearview Rod



Spare slats will be numbered to show which line item the slat is for



Screws



Hinge screws will complement the hinge finish. All orders will receive **60mm** long black screws for fixing the frames. For deeper frames, holes will be countersunk. For frames that request very large buildouts, the customer may need to source longer screws.

Frame Build Out







A frame **build out** can be requested when you need a deeper frame. Build outs are available on Hybrawood and Wood orders (not Waterproof). You can print out frame templates with your preferred build out size from our measure guides. These templates can be printed out to scale and use during your survey. When placing your order please add a note in the special notes section to confirm the build out size you require on your chosen frame.

All details will be fully discussed with you when you receive our 'Checking your Order" phone call. Any request for a frame build out will be noted in your final order details for you to sign and accept.

Should you need support with frames please feel free to speak to our expert team before you start to survey or place your order.

Frame Holes

Manufacturing will supply fixing holes (inside insert strip frames) if your order selects (yes) for pre-drilled holes. Frame holes are supplied every 600mm. The first hole starts @ 100mm from the inside tip of the end of the frame.

Frame ID Stamps




The frame ID will show either T, B, L, R to indicate the side of frame. It also shows the orders line number.

T Posts ID Stamp



There will be a stamp to show the T post location for example this is T2 - T post location 2

How Panels Are Numbered



Panels are numbered 1,2,3 etc, working from left to right.

For tier on tier, the same applies with the numbers 'wrapping' down to the lower tier.

Panel Identification

Panels will be stamped on the bottom except for tier on tier orders. For tier on tier, ID stamps are found on the top of the top tier panel and the bottom of the lower tier panels. Stained Shutters will not have the colour code stamped into the panel.







Light Block


You may request this for shutters where you need a light block and magnet plates to work with a 3 sided frame. It is a separate component piece which is generally screwed to the windowsill or floor.




Wood Slat Sizes













Hybrawood and Waterproof Ranges - Aluminium Core Strength









Our paint

- We have moved to a NC (Nitro Cellulose) paint as an increasing number of our customers have expressed a preference for this paint type.
- All components receive 3 thin layers of white Gesso to prepare the surface for painting, then 1 layer of water based paint, 1 layer of a tough PU primer, 1 layer of NC Base Paint, and then 1 layer of Final NC paint.

Our Paint Benefits

- NC dries much quicker vs PU
- This ensures manufacturing leads times can be fast, while not compromising quality (e.g. packing order with potentially wet paint spots)
- It meets our customers desire to be a more environmentally friendly paint finish to offer their customers
- Importantly, the environmental benefits offered by NC ensures our production can operate uninterrupted by strict Chinese Govt legislation to improve the environment

Touch up paint



One bottle of touch up paint with 2 swabs will be provided in the frame box of item 1 of the order.


The In's & Outs of Our Shutters

Box Labels and The Packing System

The label confirms the content via **Goods**. The order number is now on **Top**

	THE RESERVE THE PROPERTY OF THE PARTY OF THE
	Order Number
Client Reference	e:
Dealer Name:	
Tag/Customer:	
Item Numbur:	1
Room:	LOUNGE
Goods:	LL
Box No:	1 / 5
Order No:	

	Order Number
Client Reference	:
Dealer Name:	
Tag/Customer:	
Item Numbur:	1
Room:	LOUNGE
Goods:	Frame 🔨
Box No:	5 1 5
Order No:	



The panel box label will show the panel configuration of the panels inside the box via Goods.

The frame box label will have Frame in Goods.

If there are up to 2 T-posts in the shutter, these will be included in the frame box. It will have the T-posts numbers written next to Frame.

If there are over 2 T-posts in the shutter, these will be packaged in a separate box to the frame. Please be aware that the box will still state Frame under Goods. It will have the T-post numbers written next to frame.

Battens will be packaged with the corresponding frame for each line when the number of battens is small. If there are a lot of battens, these will be packaged separately in one box. Battens will be indicated on the label by having BA written in the Goods section.







All hardware will be in the accessories box. The label for accessories box location is clear.

Box 1/5 means this order should have 5 boxes in total and this label is for box number 1.

How to Measure

Visit https://shutters.co.uk/measure to select & print the required measure guide and our frame templates.

How to Fit

Visit https://shutters.co.uk/install to select & print our installation guide.

Key Facts Regarding Shutters

Once surveyed, changes must not be made to the window or surrounding area. Changes could affect the fitting of bespoke shutters (e.g. wall plaster, new tap or windowsill or window handles).

Not all windows are square, so you may need to use decorators caulk or trim to ensure shutters fit 100% level in some openings.

There may be obstructions like skirting boards or dado rails which will need to be altered.

Shutters are not a blackout product and there may be small light gaps around shutters, especially with 3- sided frame installations.

Café shutters cover the lower section of the window only & usually they are fitted with a 3-sided frame with no piece of frame on the top.

Full height shutters are best fitted with 4 sided frames. Panels can have a dividing rail inserted or a split in the Clearview or Hidden rod mechanism. All options will allow separate movement of slats on top and bottom. However, a full height panel will always move as one.

Tier on tier shutters need a 4- sided frame. Tier on tier means top and bottom panels are separate and can open and function independently from each other. This design is best suited to taller or narrow windows. Wider windows are often best fitted with full height shutter panels. We can supply T posts to support wider installations.

Inward opening windows require special consideration. Window functionality could be restricted after shutters are installed, this should be explained at the point of survey. We offer Vintage L frames which can help overcome such challenges.

Items which can restrict the shutter fitting should be removed prior to installation (e.g. BT boxes, alarm boxes, curtains and poles, large furniture)

Should you require assistance please do not hesitate to contact our Customer Services team on 0800 074 7321 or you can email hello@theshutterstore.co.uk

